



High Speed Lathe Machine Model : 460x1000

Capacity	
Height of centers	230 mm.
Swing over bed	460 mm.
Swing over gap × width	690 × 165 mm.
Swing over cross slide	270 mm.
Distance between centers	1000 mm.
Width of bed	300 mm.
Cutting Tool Max. Section	25 × 25 mm.
Travel of cross slide	285 mm.
Travel of top slide	130 mm.
Headstock and main spindle	
Spindle taper	MT6
Spindle bore	58 mm.
Spindle Nose	D1-6
Spindle Speed Number	12
Range of spindle speeds	25 ~ 2000 rpm
Tailstock	
Tailstock quill diameter	60 mm.
Tailstock quill travel	130 mm.
Taper of tailstock quill	MT4

Threads and Feeds	
Lead screw Diameter & Thread	Ø35 mm. × 4 T.P.I. or Pitch 6 mm.
Metric threads range	0.1 ~ 14 mm.
Imperial threads range	2 ~ 112 T.P.I.
Longitudinal feeds Metric	0.031-1.7mm/Rev
Longitudinal feeds Imperial	0.0011"-0.0633"/Rev
Cross feeds Metric	0.014-0.784 mm
Cross feeds Imperial	0.00033"-0.01837"
M.P threads range	0.1 ~ 7 m
D.P threads range	4 ~ 112 DP
Motor	
Main motor	5.5 kW (7.5 HP)
Coolant pump	0.1 kW (1/8 HP)
Measurement	
Machine Space Required (L × W × H)	2200 × 1080 × 1370
Net Weight / Gross Weight	1645 kg / 1910 kg

ติดต่อสอบถาม

Tel : 02-101-0235 (สำนักงานใหญ่) Tel : 085-549-9956 (สิระกานูจน์)
 Tel : 090-927-3182 (นิวัฒน์) Tel : 062-894-9556 (ฐานิตา)
 Tel : 092-294-9922 (พัฒนจิตตา) Tel : 084-239-5922 (นิตยา)